



## SPECIFICATIONS

Product Description: **8" PLASTIC COM-PAX-IAL BLOWER (220V/50 Hz)**  
Part Number: **9533-E, 9533-15E, 9533-25E**  
Style: **AXIAL FAN 8" (20cm) - WITH OR WITHOUT CANISTER**

### GENERAL DESCRIPTION:

High output from a compact axial blower, designed for easy use and storage without sacrificing airflow. Available as blower only or complete unit with 15' (4.75m) or 25' (7.62m) of ducting and storage canister. Canister attaches to intake or output of blower for suction or ventilation.

### CONSTRUCTION:

- Polyethylene housing & canister assembly
- Lightweight, corrosion, UV, and chemical resistant
- Durable construction design and super quiet.
- Bottom enclosure to protect electrical components
- Steel/powder coated grill
- Carry handle molded into blower and canister housing
- Equipped with five (5) feet

### MOTOR:

HP: 1/3 HP  
Voltage/Hz: 220V AC, 50 Hz, Single Phase  
RPM: 2800 (loaded at 220V, 50 Hz)  
Switch: ON/OFF Rocker  
Amps: 1.9A  
Cord: 15' (4.57m) AWG

### FAN:

- Polypropylene nine blade fan

### DUCTING: (included on 9533-15 and 9533-25 models)

- Single-Ply Lightweight Vinyl/polyester, PVC coated 150°F Temp resistant. Non-Collapsible Retractable design.
- Class 1 hard drawn spring steel wire helix, ASTM 227 Specs. Yellow with black wear-strip and integrated nylon attachment strap

### BLOWER DIMENSIONS:

Blower P/N	Length In (cm)	Width In (cm)	Height In (cm)	Weight Lbs (Kg)
9533	13 1/4" (33.6)	12" (30.4)	13 3/4" (34.9)	17 (7.7)
9533-15	32" (81.2)	13 1/2" (34.2)	14 1/2" (36.83)	33 (14.9)
9533-25	32" (81.2)	13 1/2" (34.2)	14 1/2" (36.83)	38 (17.2)

### FLOW RATES: (CFM calculated using 15' (4.57m) of 8" (20.3cm) ducting)

Free Air CFM (m <sup>3</sup> /hr)	One 90° Bend CFM (m <sup>3</sup> /hr)	Two 90° Bends CFM (m <sup>3</sup> /hr)
831 (1411.87)	709 (1204.59)	586 (995.62)

