

Codan 8516 Breathing Hose



Codan 8516 - EN 14593 / EN 14594 (EN139)

Flexible, black antistatic hose with one laminated green stripe in accordance with EN 14593/EN 14594. Available in other colours to order. For carrying breathing air at high pressure from compressor to filter. Good ozone resistance and external resistance to several chemicals. Ideal for use when cleaning tanks, etc. or where the outer surface of the hose is exposed to adverse conditions. Installed using brass or stainless crimped-on fittings. Choice of connector should be considered carefully. Also according to EN 139: 1994. Please contact Codan for further information.

Type nr. 8516

Application: Compressed Air

Standard Length: 50 metres

Working Temperature: -30°C to 100°C

Inside: NBR

Colour: Black

Reinforcement: PVA

Outside: NBR/PVC

Colour: Black

Standards: EN 14593 / EN 14594 (EN139)

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
6,3	15,3	10	60	62	192	8516006000
7,0	16,4	10	60	66	217	8516007000
9,5	19,5	10	60	78	286	8516010000
12,7	22,7	10	60	104	381	8516013000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. Written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage

of vulcanised Rubber Products). The individual conditions of an application will affect the life time of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification.

Please contact Codan Rubber for individual product manufacturing tolerances.



Codan Rubber A/S Værkstedvej 45-49, DK-4600 Køge, Denmark Tel. +45 56 64 64 64 Fax +45 56 64 65 48
Mail: info@codan.com www.codan.com

29/08/2016